



Regular Thin Set

Micro Milling Thin set mortar is a blend of Portland cement sand and special additives for the installation of ceramic tiles on concrete substrates.

Features:

- Suitable for installing ceramic tiles, clay tiles, cement tiles, quarry tiles, brick pavers and other porous tiles.
- For Commercial or Residential use.
- For Interior and exterior use.
- For floors and walls.
- Ideal for installing tile over concrete substrates.
- Specially formulated for warm weather conditions.
- Exceeds ANSI A118.1 standard for Dry-set Portland Cement tile mortar.
- Mix with water only.



Available in 22.7kg/ 50 lbs size.

Mixing:

One 22.7 kg./ 50 lb. bag should be mixed with 4.6 -5.0 L (4.9 -5.3 U.S. Qts.) of clean, cool potable water.

Coverage:

Using a 1/4" x 1/4" (6x6mm) notched trowel on an evenly prepared surface, one bag will cover 30-50 sq. ft. (2.78- 4.65 m²).



Premium 2600

Micro Milling Premium 2600 Thin set is a blend of Portland cement, graded sand and special additives (including redispersible polymers which are designed to improve adhesion and provide greater bond strength).

Features:

- Suitable for installing porcelain tiles, ceramic tiles, clay tiles, cement tiles, glass tiles, quarry tiles, brick pavers, marble, natural stone and other non-porous tiles.
- For Commercial or Residential use.
- For Interior and exterior.
- For floors and walls.
- Ideal for installing tile (including porcelain) over concrete substrates.
- Specially formulated for warm weather conditions.
- Exceeds ANSI A118.4 standard for modified dry-set Portland cement tile mortar.
- Polymer Modified
- Mix with water only.



Available in 22.7kg/ 50 lbs size.

Mixing:

One 22.7 kg. / 50 lb. bag should be mixed with 4.8 -5.2 L (5.1 -5.5 U.S. Qts.) of clean, cool potable water.

Coverage:

Using a 1/4 "x1/4 " (6x6mm) notched trowel on an evenly prepared surface, one bag will cover 30-50 sq. ft. (2.78- 4.65 m²).



Premium 3600

A high-quality polymer modified dry-set mortar blend of Portland cement, graded sand and special additives including redispersible polymers which are designed to improve adhesion and flexural strength, provide greater bond strength, and enhanced resistance to shock and impact.

Features:

- Suitable for installing porcelain tiles, ceramic tiles, clay tiles, cement tiles, glass tiles, quarry tiles, brick pavers, marble, natural stone, tile over tile* and tile over terrazzo*.
- For Commercial or Residential use.
- For Interior and exterior.
- For floors and walls.
- Superior flexibility and bond strength -best for installing tile (including porcelain) over difficult substrates.
- Specially formulated for warm weather conditions.
- Resistant to shock and impact
- Exceeds ANSI A118.4 standard for modified dry-set Portland cement tile mortar.
- Polymer Modified



Available in 22.7kg/ 50 lbs size.

Mixing:

One 22.7 kg./ 50 lb. bag should be mixed with 4.6 -5.0 L (4.9 -5.3 U.S. Qts.) of clean, cool potable water.

Coverage:

Using a 1/4 "x1/4 " (6x6mm) notched trowel on an evenly prepared surface, one bag will cover 30-50 sq. ft. (2.78- 4.65 m²).



Premium LFT

Micro Milling Premium LFT thin set or medium-bed mortar is a polymer modified blend of Portland cement, graded sand and special additives for the installation of large format tiles.

Features:

- Ideal for installing 15" x 15" (38x 38 cm) and larger tiles.
- Suitable for porcelain tiles, ceramic tiles, marble and natural stone, tile over tile* and tile over terrazzo* applications.
- For Commercial or Residential uses.
- For Interior and exterior.
- For floors and walls.
- Ideal for installing tile (including porcelain) over concrete substrates.
- Can be used as a medium bed mortar up to $\frac{3}{4}$ " (19mm) thick.
- Special non slump formula helps eliminate lippage.
- Exceeds ANSI A118.4 standard for modified dry-set Portland cement tile mortar.
- Polymer Modified
- Mix with water only.



Available in 22.7kg/ 50 lbs size.

Mixing:

One 22.7 kg./ 50 lb. bag should be mixed with 4.6 -5.0 L (4.9 -5.3 U.S. Qts.) of clean, cool potable water.

Coverage:

Using a $\frac{1}{4}$ " x $\frac{1}{4}$ " (6x6mm) notched trowel on an evenly prepared surface, one bag will cover 30-50 sq. ft. (2.78- 4.65 m²).



Sanded Grout

Micro Milling Polymer Modified Sanded Grout is a factory prepared mixture of Portland cement, sand, calcium carbonate and special additives to which only water is added.

Features:

- Suitable for grouting the following types of tile: ceramic, porcelain, cement, glass and quarry tiles, marble and natural stone.
- For joints $\frac{1}{8}$ " - $\frac{5}{8}$ " (3-16 mm) wide
- Suitable for floors and walls.
- For Interior and exterior use.
- Commercial or Residential use.
- Water beading formula helps repel most stains, dirt and grime.
- Meets ANSI A118.7 standard for High Performance cement grouts for tile installation.
- Polymer Modified.
- Available in 24 colours.
- Mix with water only.



Available in 11.35 kg./25 lb. & 2.27 kg. /5 lb. sizes

Mixing:

One 11.35 kg. / 25 lb. bag should be mixed with approx. 2.15 - 2.25 L (2.3 - 2.4 U.S. Qts.); and the 2.27 kg. / 5 lb. sack should be mixed with approx. 445- 455 ml (15-16 fl. oz.) of clean, cool potable water.



Unsanded Grout

Micro Milling Polymer Modified Unsanded Grout is a factory prepared mixture of Portland cement, calcium carbonate and special additives to which only water is added.

Features:

- Suitable for grouting the following types of tile: ceramic, porcelain, cement, glass and quarry tiles, marble and natural stone.
- For joints 1/16" - 1/8" (1.5- 3 mm) wide
- Suitable for floors and walls.
- For Interior and exterior use.
- Commercial or Residential use.
- Water beading formula helps repel most stains, dirt and grime.
- Meets ANSI A118.6 standard for Standard cement grouts for tile installation.
- Polymer Modified.
- Available in 11 colours.
- Mix with water only.



Available in 11.35 kg./25 lb. &
2.27 kg. /5 lb. sizes

Mixing:

One 11.35 kg. / 25 lb. bag should be mixed with approx. 3.6 -3.7 L (3.8 -3.9 U.S. Qts.) and the 2.27 kg. /5 lb. sack should be mixed with approx. 710- 715 ml / 24 fl. oz. of clean, cool potable water.



Plaster Mix

Micro Milling Plaster Mix is a blend of cement, graded sand and special additives.

Features:

- Made with Graded Sand, cement and special additives.
- Used for plastering of walls, brick and block laying, stone work and patching damaged mortar.
- Ease of application
- Excellent workability
- Specially formulated for warm weather applications.
- For interior and exterior installations, floors and ceilings.



Available in 22.7kg/ 50 lbs size.

Mixing:

One 22.7 kg./ 50 lb. bag should be mixed with 4.6 -5.0 L (4.9 -5.3 U.S. Qts.) of clean, cool potable water. *Need accurate copy*



Concrete Mix

Micro Milling Concrete Mix is a mixture of sand, 1/4" fine aggregates and cement used for repairing concrete and constructing foundations. Ideal for setting posts, anchoring poles, casting new driveways, walkways and steps.

Features:

- Made from 1/4" aggregate, sand and cement
- Used for repairing of concrete, constructing foundations, setting posts, casting driveways, walkways and steps.
- Ease of application
- Excellent workability
- Advantages include high strength and premixed for even consistency.



Available in 22.7kg/ 50 lbs size.

Mixing:

One 22.7 kg./ 50 lb. bag should be mixed with 4.6 -5.0 L (4.9 -5.3 U.S. Qts.) of clean, cool potable water. *Need accurate copy*



Micro Level 5000

Micro Milling's Micro Level 5000 is a self-levelling, concrete underlayment that is designed for use over various substrates to achieve a flat and level floor base.

Features:

- Fast drying
- Low shrinkage
- High compressive strength > 5000 psi
- Allows foot traffic in 6 hours and accepts Tile & Stone after 24 -48 hours
- Advantages include high strength and premixed for even consistency.



Available in 22.7kg/ 50 lbs size.

Mixing:

One 22.7 kg./ 50 lb. bag should be mixed with 4.6 -5.0 L (4.9 -5.3 U.S. Qts.) of clean, cool potable water.