



Safety Data Sheet (SDS)

Read complete SDS prior to using product.

Micro Milling Plaster Mix

1. PRODUCT IDENTIFICATION

Product Trade Name: Micro Milling Plaster Mix

Name, Address, Phone Number of the Manufacturer

Company: MICRO MILLING LIMITED
Claxton Bay P.O. Box 4235
Plaisance Park Industrial Estate,
Pointe-a-Pierre,
Trinidad & Tobago, W.I.
Telephone #: 1(868) 659-4060
Website: www.micromillingtt.com

Recommended Use: Plastering walls, brick laying, stone masonry and patching damaged mortar.

Restrictions on Use: The presence of respirable dust and respirable crystalline silica require appropriate care in the use and handling of this product.

2. HAZARD IDENTIFICATION

GHS Hazard Symbols



Physical Hazards

Not Classified

Health Hazards

Skin Irritation:

Category 2

Eye damage/irritation:

Category 1

Sensitisation, Skin:

Category 1

Carcinogenicity:

Category 1A

Specific Target Organ toxicity, single exposure

Category 3 (respiratory tract irritation)

Specific Target Organ toxicity, repeat exposure

Category 2 (lung)

Hazard Statements

Corrosive. Causes skin irritation. May cause allergic skin reaction.

Causes eye damage. In case of contact with eyes rinse repeatedly with water and call physician.

May be harmful if swallowed.

Contains free silica (Crystalline quartz). Prolonged/repeated breathing of dust may cause delayed lung injury (silicosis). May cause cancer

Precautionary Statements

Prevention

Do not handle until all safety precautions have been read and understood. During mixing or application avoid contact with eyes and skin. In case of contact with eyes, rinse repeatedly with water and call a physician. Do not breathe dust. Follow OSHA safety and health standards for crystalline silica (quartz)

Use personal protective equipment (gloves, boots, goggles, and respirator/mask) when handling or using this product. Wash thoroughly after handling.

Access our PDS online for more information on the safe and proper use of this product.

Response If on skin: Wash with soap and water. If skin irritation or rash occurs, seek medical advice/attention
 If in eyes: Wash eyes immediately and repeatedly with water and seek medical attention.
 If ingested: Do not induce vomiting. Rinse mouth with water and drink water. Obtain immediate medical attention.
 If inhaled: Remove person immediately to fresh air and ensure comfortable breathing resumes. Give artificial respiration if needed and seek medical attention

Storage Store off the ground, on pallets in original unopened packages in a dry, well ventilated areas for the best life expectancy. Should not be exposed to water, direct sunlight and /or damp conditions prior to use.

Disposal Dispose of contents/containers in accordance with local/regional/international regulations.

Hazards not otherwise classified (HNOC)
 None known

Supplemental information
 Product becomes alkaline when exposed to moisture

3. COMPOSITION /INFORMATION ON INGREDIENTS

List of mixture components

Chemical Name	CAS Number	%
Silica Sand, Crystalline Silica (Quartz)	14808-60-7	60- 70
Portland Cement	65997-15-1	30- 40

Other components below reportable levels

Composition: All concentrations are in percent by weight.

4. FIRST AID MEASURES

Description of First Aid Measures

Eye Contact:

Flush eyes immediately washing with cool water for a few minutes while holding eyelid open. Remove contact lens if worn and rinse repeatedly with water. If irritation persists, seek medical attention.

Skin Contact:

Remove contaminated clothing if any and wash exposed skin with soap and water immediately. If irritation persists, seek medical attention.

Ingestion:

If ingested do not induce vomiting. Rinse mouth with water. Drink water. Seek immediate medical attention

Inhalation:

If dust concentrations are exceeded remove the person immediately to fresh air. Seek medical attention as needed if distress persists.

Gross Inhalation:

If there is a gross inhalation of crystalline silica (quartz), remove the person immediately to fresh air. If not breathing, trained personnel should initiate artificial respiration as needed. Obtain immediate medical attention.

5. FIRE FIGHTING MEASURES

Flash Point: Will not burn except under extreme temperatures

Extinguishing Media:

Water spray. Water Fog. Carbon dioxide (CO²). Dry Chemical Powder. Foam
 Other appropriate fire extinguishing media.

Unsuitable Extinguishing Media: None in particular

Specific hazards arising from the product's chemical composition:

Burning produces heavy smoke.

Hazardous combustion products:

Hazardous combustion products may include Carbon Oxides.

Special protective equipment and precautions for firefighting personnel:

Wear standard fire-fighting gear with suitable self-contained breathing apparatus

Move undamaged containers or bags from immediate hazard area if it can be safely done

Explosive properties: No unusual explosion hazards noted

Oxidising properties: None noted

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away, cordon off area if possible. Ensure appropriate PPE and clothing is worn by personnel before and during clean up

Steps to be taken in case material is released or spilled:

Use Appropriate Respiratory Protection if dry. Use NIOSH/OSHA approved respirator if dust exposure level exceeds the exposure limit.

Use Appropriate Boots and gloves if wet. Do not handle damaged containers or spilled materials unless wearing appropriate protective clothing.

Methods and Materials for containment and clean up

Spillage when dry

Limit dust with water spray. Promptly clean by scoop, shovel and/ or vacuum if spilled when dry. Provide ventilation.

Spillage when wet

Contain spill by dykeing with inert absorbent materials to control material flow and if possible, return to batch mix if material is uncontaminated.

If contaminated, place in an appropriate container for waste or disposal. Do not dispose of via drainage pipes, canals, drains or waterways.

Following removal of spilled material, wash area with water.

Refer to State and Local Regulations for handling solid waste.

7. HANDLING AND STORAGE

Precautions for safe Handling & Use

Use only in applications as stated on the label.

Use appropriate bending and lifting techniques when handling unopened bags.

Ensure bag/container is properly closed after use

Avoid skin and eye contact. Always wear appropriate personal protective equipment (PPE) - respirator, gloves, goggles or protective glasses and boots - when moving or using product

Ensure adequate ventilation in work area. Ventilate with fresh air, including opening doors and windows should be observed during any floor/wall tile installation.

Operate HVAC systems at 100% fresh air intake before, during and after installation to eliminate lingering odors or particulate matter.

Do not eat drink or smoke while working. Do not take internally.

Precautions for safe Storage

Store unopened bags on pallets in original packaging in a dry and cool location

Should not be exposed to water, direct sunlight and damp prior to use

Do not store opened bags

Incompatible materials:

Contact with powerful oxidising agents such as fluorine, chlorine, tri-fluoride and oxygen di-fluoride may cause fires.

8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

Control Parameters

List of components with OEL

Component	OEL Type	Long Term mg/m ³
Silica Sand, Crystalline Silica	ACGIH-TWA (mg/m ³)	0.025 mg/m ³
Portland Cement	ACGIH-TWA (mg/m ³)	1 mg/m ³ (particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter

Appropriate Engineering Controls:

Use ventilation adequate to keep exposure levels of airborne dust, fume, vapour and other contaminants below recommended exposure limits.

Ensure good ventilation to prevent and remove build-up of any dust generated during handling or use.

Individual Protection Measures:

Eye protection: Wear safety glasses or protective goggles that are close fitting to avoid splashed droplets

Protection for hands: Use protective gloves of leather, neoprene or nitrile rubber gloves for hands

Protection for skin: Clothing of cotton, denim or rubber that provides comprehensive protection

Respiratory protection: Use appropriate Occupational Safety & Health approved respirator or dust mask for adequate protection. e.g. NIOSH approved (30 CFR 11)

Ensure proper ventilation. Open all available windows and entrances to ensure good ventilation.



Safety Gloves



Safety Goggles



Safety Boot



Dust Respirator

General Hygiene:

Periodically wash areas contacted by wet or dry cement products. If clothing becomes soiled with wet or dry cement products, it should be removed and replaced with clean dry clothing. Wash contaminated clothing as soon as possible.

9. PHYSICAL AND CHEMICAL PROPERTIES**Information on basic physical and chemical properties**

Physical State: Solid
Form: Powder- Fine Textured Powder.
Colour: Grey
Odour: Characteristic general cement-like odour.
Odor threshold: Not available.
Vapour Pressure: Not Available.
Vapour density: Not Available.
pH: 11.0- 13.0
Relative density: 2.2 -2.3
Melting Point/ Freezing Point: Not Available.
Solubility (in water): Insoluble
Initial boiling point and boiling range: Not Available
Flash Point: Not Available
Evaporation Rate: Not Available
Flammability (solid/gas): Not Available.
Partition coefficient (n-octanol/water): Not Available.
Auto ignition temperature: Not Available.
Decomposition temperature: Not Available.
Viscosity: Not Available.
Explosive Properties: Non-explosive.
Oxidising properties: Non oxidising.
Flammability (solid/gas): Not flammable
VOC content: 0%. Not applicable.

10. STABILITY AND REACTIVITY

- Reactivity:** No dangerous reaction known. Stable under normal conditions of use
- Chemical Stability:** Stable under normal storage conditions. Keep dry while stored.
- Possibility of hazardous reactions:** None known under conditions of normal use.
- Conditions to avoid:** Water, moisture and incompatible materials. Once bag/container is opened, contents should be used as quickly as possible. Close bags after use to prevent the absorption of moisture and/or contaminants.
- Incompatibility (materials to avoid):** Avoid contact with strong oxidising agents, powerful acids and strong bases. Avoid agents such as fluorine, chlorine, tri fluoride and oxygen di-fluoride. Wet cement-based mixtures are alkaline and is not compatible with acids, aluminum or ammonium.
- Hazardous decomposition products:** May include and are not limited to oxides of carbon.
- Hazardous Polymerisation:** None known

11 – TOXICOLOGICAL INFORMATION

Toxicological information via likely routes of exposure

- Inhalation:** Dust irritates the respiratory system, may cause coughing, sneezing and difficulty in breathing.
- Ingestion:** Swallowing may cause gastrointestinal irritation
- Skin Contact:** Causes skin irritation. May cause allergic reaction
- Eye contact:** Causes serious eye irritation

Symptoms rel. to the physical, chemical and toxicological effects:

- Skin Contact:** May cause skin irritation, including burns in the presence of moisture. Skin contact during hydration may slowly develop sufficient heat that may cause severe skin burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous contact with the skin.
- Eye Contact:** Causes serious eye irritation. Symptoms include stinging, tearing, redness, swelling and blurred vision. Permanent damage to eyes can result if exposure is prolonged
- Inhalation:** Dust irritates the respiratory system, may cause coughing, sneezing, respiratory inflammation and difficulty in breathing.
- Ingestion:** Swallowing may cause gastrointestinal irritation, stomach distress, nausea or vomiting.

Symptoms rel. to the physical, chemical and toxicological effects:

- Rash, coughing, Irritant effects. Symptoms include stinging, tearing, redness, swelling and blurred vision. Permanent damage to eyes can result if exposure is prolonged.
- Acute Toxicity:** May cause respiratory irritation
- Skin Corrosion/ Irritation:** Yes
- Eye damage /irritation:** Yes
- Respiratory Sensitisation:** No data available
- Skin Irritation:** May cause allergic reaction

- Germ cell mutagenicity:** No data available to indicate the product or any component present at greater than 0.1% are mutagenic or geno-toxic.

Toxicological information on the main components of the mixture:

Silica Sand (Crystalline Silica) a) acute toxicity LD50 Oral rat = 500mg/kg

Carcinogenicity: Silica Sand (Crystalline Silica)

Can cause cancer by prolonged repeated inhalation. This product has the potential to generate respirable dust during handling and use. Dust may contain respirable crystalline silica. Crystalline silica has been classified by the IARC, NTP and ACGIH as a known human carcinogen and suspected human carcinogen respectively. Overexposure to dust may result in pneumoconiosis, a respiratory disease caused by the inhalation of mineral dust which can lead to fibrotic changes to the lung tissue or silicosis, a respiratory disease caused by the inhalation of silica dust which can lead to the inflammation and fibrosis of the lung tissue. Occupational exposure to respirable dust and respirable crystalline silica should be monitored and controlled.

May cause delayed lung injury.

IARC Monographs. Overall evaluation of Carcinogenicity

Crystalline Silica (CAS 14808-60-7) 1- Carcinogenic to humans

NTP Report on Carcinogens

Crystalline Silica (CAS 14808-60-7) Known to be a Human Carcinogen

OSHA Specifically Regulated Substances (29 CFR 1810.1001-1050)

Not Regulated

Reproductive toxicity: This product is not expected to cause reproductive or developmental defects

Specific Target Organ toxicity (single exposure): May cause respiratory irritation

Specific Target Organ toxicity (repeated exposure): May cause damage to lungs

Aspiration hazard: Not a known aspiration hazard

Chronic Effects:

The adverse health effects associated with exposure to crystalline silica (quartz) which can include silicosis, lung cancer, scleroderma, tuberculosis, pneumoconiosis and nephrotoxicity result are chronic effects associated with long term exposure.

12– ECOLOGICAL INFORMATION

Ecology - General

No ecological impact when used according to directions. Normal dilution of this product to drains, sewers, septic systems and treatment plants is not considered environmentally. Use good working practices and keep good workplace sanitation to minimize /prevent the contamination of the environment by the product.

There is no chronic or acute ecological impact when product is used according to directions.

The normal dilution of this product during cleanup with water after use, and which may make its way to drains, sewers or watercourses is generally not considered harmful. Nevertheless, the manufacturer advises this practice should be limited or avoided if possible.

Persistence and Degradability:	No data available.
Bio accumulative Potential:	No data available.
Soil to Groundwater Contamination:	The product is not mobile in soil.
Other Adverse Effects:	No other adverse effects including ozone depletion, endocrine disruption or global warming potential is expected.

13 – DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste must be handled in accordance with any and all applicable state, provincial, federal, county and local regulations. Consult local authorities before disposal of product.

Do not dispose of unused or contaminated product in drains, watercourses and sewer systems.

14 –TRANSPORT INFORMATION

Basic Shipping description:	In accordance with TDG
IMDG	No classified as dangerous goods
IATA	No additional information available
Transport Information/DOT:	No additional information available
Transport of Dangerous Goods:	Not regulated for transport

15 – REGULATORY INFORMATION

Country Regulations

National EMA – Not listed as a Certified substance requiring Environmental Certification Regulation
Ministry of Health- Pesticides & Toxicological Inspectorate – Not listed.

Summary of abbreviations and acronyms used in the safety data sheet

ACGIH: American Conference of Governmental Industrial Hygienists

IMDG: International Maritime Code for Dangerous Goods

CEC: Certificate of Environmental Clearance

IATA: International Air Transport Association


IATA-DGR: Dangerous Goods Regulation by the “International Air Transport Association” (IATA)

EMA: Environmental Management Agency, Trinidad & Tobago

OEL: Occupational Exposure Limit
CAS: Chemical Abstracts Service (division of the American Chemical Society)
TLV: Threshold Limit Value
TWATLV: Threshold Limit Value for the Time Weighted Average 8-hour day (ACGIH Standards)
STEL: Short Term Exposure Limit
STOT: Specific Target Organ Toxicity

16 – OTHER INFORMATION

HMIS Ratings NFPA Health: 2= Moderate
 NFPA Flammability: 0
 NFPA Physical Hazard: 0
 NFPA Special Risk: n.a.



Issue Date: 04 October 2021
Version # 01

Disclaimer: This Safety Data Sheet (SDS) has been prepared in good faith on the basis of information available at the time of publication. It is intended to provide users with information and guidelines for the safe and proper use of our product. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof.
Micro Milling Limited assumes no responsibility for personal injury or property damage to vendees, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of the product. Further the manufacturer warrants that this product shall be of saleable quality when used in accordance with stated instructions. This product is not warranted as suited for any purpose other than the general use(s) for which it is intended.